

Eco Series UPS

800VA



Installing an Eco UPS provides reliable and clean power to your valuable equipment. The UPS blocks surges, spikes and prevents a power outage, ensuring that your equipment is operating 24/7.

All eco series UPS are a multipurpose design suitable for CCTV, computers, point of sale, modems & NBN's. All UPS run times are pre-calculated for your ease.



RUNTIME IN MINUTES

							CCTV			
Load VA/W	100VA 60W	200VA 120W	400VA 240W	500VA 300W	600VA 360W	800VA 480W	NVR + 4 Camer- as	NVR + 8 cameras	NVR + 12 cameras	NVR + 16 cameras
ECO800L	60	28	10	3	1	-	25	15	7	2



Not sure what kind of UPS you need to keep everything running safe and smoothly when power is irregular? Check out our [UPS Calculator](#) to find your solution.



User Manual

Model	ECO800L				
Capacity	800VA/480W				
Display	LCD				
Input					
Input Voltage	230 VAC				
AVR voltage range	162-290 VAC				
Frequency range	50Hz ± 10%				
Output					
Voltage regulation	230 VAC ± 10%				
Frequency	Batt. Mode 50Hz, +/- 1%				
Waveform	Modified/Simulated Sine Wave				
Transfer time	Typical 2-6ms				
Output sockets	3x Aus Standard 10A & 3x Surge protected only				
Battery					
Type	Sealed lead acid				
Configuration	1 x 12V/9AH				
Charge current(Max)	2A				
Recharge	6-8 hours to 90% capacity after complete discharge				
Communications and management					
Communication	USB				
Network surge protection	RJ45				
Software supplied	UPSilon				
DC start	Yes				
Auto restart	Yes				
AVR	Yes				
Surge protection	125Joules / 4500A				
Short circuit	User Replaceable Fuses on overload				
Display indication &audible alarms	LCD: Input & Output Voltage, Battery level, Load level, UPS status. LED: Mains present, battery charge, mains fail, fault.				
Environment					
Audible noise	Less Than 30dB				
Temperature	0 - 40 Degrees C				
Humidity	0-90% RH (Non-Condensing)				
Physical dimensions					
Dimensions (HxWxD) mm	95x200x293				
Shipping Dimensions (HxWxD) mm	245x130x360				
Net weight	4Kg	5.2Kg	7.7Kg	10.6Kg	11.1Kg